

Reply to Office Action and Amendment under 37 CFR §1.116
Serial No. 09/393,482

Page 2

an inner sleeve having a first end, a second end opposite said first end, and a pair of annular upset beads therebetween, said inner sleeve further having an inner diameter and an outer diameter thereon, said outer diameter having at least one projection thereon;

a hose having an inner diameter positioned over said outer diameter of said inner sleeve, said at least one projection of said inner sleeve interlocking with said hose to resist axial movement of said hose relative to said reinforced hose coupling;

an outer sleeve having a terminating end sandwiched between said pair of annular upset beads of said inner sleeve to prevent axial movement relative to said inner sleeve, said outer sleeve further having an inner diameter circumscribing said hose, said inner diameter of said outer sleeve further including at least one depression therein formed by a crimping operation, said at least one depression defining [a crimp area] an area of peak crimp force of a predetermined longitudinal extent and interlocking with said hose to further resist axial movement of said hose relative to said reinforced hose coupling; and

at least one reinforcing ring positioned within said inner diameter of said inner sleeve within said predetermined longitudinal extent defined by said area of peak crimp force [crimp area], whereby said at least one reinforcing ring provides localized support along said predetermined longitudinal extent to resist deformation of said inner sleeve during said crimping operation.

D

Reply to Office Action and Amendment under 37 CFR §1.116
Serial No. 09/393,482

Page 3

11. (Twice Amended) A reinforced hose coupling defining [a crimp area] an area of peak crimp force of a predetermined longitudinal extent, said reinforced hose coupling comprising:

a hose having an outer diameter and an inner diameter;

an outer sleeve having an inner diameter circumscribing said outer diameter of said hose, said outer sleeve further having a plurality of depressions therein, said plurality of depressions defining [a crimp area] an area of peak crimp force of a predetermined longitudinal extent and interlocking with said hose to resist axial movement of said hose relative to said outer sleeve;

an inner sleeve having an inner diameter and an outer diameter, said inner sleeve being adapted to be inserted into said inner diameter of said hose said inner sleeve having at least one projection interlocking with said hose to resist axial movement of said hose relative to said inner sleeve; and

at least one reinforcing ring situated within said inner diameter of said inner sleeve, within said predetermined longitudinal extent defined by said [crimp area,] area of peak crimp force, whereby said at least one reinforcing ring positioned between said plurality of depressions of said outer sleeve such that] said at least one reinforcing ring provides localized support along said predetermined longitudinal extent to resist deformation of said inner sleeve.

12. (Twice Amended) A reinforced hose coupling defining [a crimp area] an area of peak crimp force of a predetermined longitudinal extent, said reinforced hose coupling comprising:

D

Reply to Office Action and Amendment under 37 CFR §1.116
Serial No. 09/393,482

Page 4

a hose having an outer diameter and an inner diameter;
an outer sleeve having an inner diameter circumscribing said outer diameter of said hose, said outer sleeve further having at least one depression therein, said at least one depression defining [a crimp area] an area of peak crimp force of a predetermined longitudinal extent and interlocking with said hose to resist axial movement of said hose relative to said outer sleeve;

an inner sleeve having an inner diameter and an outer diameter, said inner sleeve being adapted to be inserted into said inner diameter of said hose said inner sleeve having at least one projection interlocking with said hose to resist axial movement of said hose relative to said inner sleeve; and at least one reinforcing ring situated within said inner diameter of said inner sleeve, within said predetermined longitudinal extent defined by said [crimp area] area of peak crimp force, whereby said at least one reinforcing ring provides localized support along said predetermined longitudinal extent to resist deformation of said inner sleeve.

Remarks

To highlight the distinction of the above referenced invention over the prior art as interpreted by the Examiner in the Office Action of October 22, 2001, Paper No. 10, and the subsequent Advisory Action of January 9, 2002, Paper No. 13, the claims were amended as set forth herein. Claims 1, 11 and 12 were amended to more clearly define the subject matter of the invention and to place all of the claims remaining in the application in condition for allowance. No new matter was presented and entry thereof is respectfully requested.

D